

LINCH TECH CONF LSC-22 DIRECTOR'S CONSOLE

Conference Microphone Set

LINCH TECH CONF LSC-22 DIRECTOR'S CONSOLE



- Complies with IEC 60914, GBT 15381-94 standards
- 2 RJ-45 ports for connecting a Cat 5/5e/6 twisted pair cable to the VIS-DCP2000-D central controller
- Digital data bus and audio 64 channels with network ring technology
- Zero audio transmission delay
- Automatic assignment of the device ID in the system
- Hot plugging and identification of remotes (Hot-swap)
- 2 3.5 Audio Jack sockets for connecting headphones
- 1 Touch MIC ON/OFF button with LED activity indicator
- 2 touch buttons for adjusting the volume of the audio channel
- 2 touch priority buttons of the chairman with LED indicator
- OLED display with a resolution of 128x32 pixels
- Sampling rate 48,000 Hz
- Frequency response 20-20000 Hz
- Sensitivity -46 dBV/Pa
- Signal-to-noise ratio 70 dB
- Maximum sound pressure 125 dB (KNI <3%)
- The maximum consumption is 2 watts
- The resistance of the earphone is 16 ohms
- Input resistance 3.5 2 kOhm
- Weight 1.1 kg
- Remote control dimensions (W x D x H): 195 x 120 x 60 mm (without gooseneck microphone)
- Color black
- Manufacturer INGS