

## LINCH TECH X30W AABL

Wall Acoustics Kit

### LINCH TECH X30W AABL



#### TECHNICAL PARAMETERS

- LINCH TECH X30W AABL has a moisture-proof housing made of durable ABS plastic, which makes it suitable for outdoor installation without direct exposure to moisture.
- Type of system: This speaker system belongs to the "bass reflex" type. It is equipped with a 4" woofer and a tweeter, which provides improved bass reproduction and a wide frequency range from 70 Hz to 20 kHz.
- Power: The INGS X30W AABL has a rated power of 30 Watts, which makes it suitable for background sound in small and medium-sized rooms.
- Built-in transformer: LINCH TECH X30W AABL equipped with an internal transformer (70V/100V), which allows you to connect multiple speakers without the risk of overloading the power amplifier. The user can choose from four output power settings (2W, 4W, 8W, 16W) using the regulator on the back panel.
- A set of two loudspeakers: It comes complete with two 2-way passive speakers, which provides stereo sound.
- Power and inputs: Provides different power modes depending on the line used: the maximum power for 100 In line is 16W / 8W/4W/2W and for 70 In line is 8W /4W/2W/1W. There are also Euroblock input connectors for easy connection.
- Sound characteristics: The sensitivity (1W/1m) is 89 dB, and the maximum SPL is 104 dB. The frequency range is from 98 Hz to 20 kHz.
- Dispersion and materials: The width and height of the dispersion are 120° x 90°. The body is made of polypropylene, and the grille is made of aluminum.
- Dimensions and weight: Overall dimensions are 148 x 210 x 134 mm, the weight of each speaker is 1.9 kg.